

R2k(FR)-G4.1

Medium intensity obstacle light for nighttime marking





Obstacle Light R2k(FR)-G4.1

For nighttime marking according to:

- French Medium intensity Obstacle Light Type B with modified beam beacon
- Certification in process

The Lanthan obstacle light is characterized by its compact design and robust construction. Its key features include:

- Internal ambient light sensor (VEML7700)
- Build-in GPS
- Capable of firmware updates (FOTA)
- Field-configurable settings



Being the first LED fire supplier in the wind industry, Lanthan provides reliable obstacle lights.

Manufactured by TWE GmbH Trade Wind Energy (part of Lanthan Group).

Article Allocation

Name / Description	Article-No.
R2k(FR)-G4.1	LAN-013937

R2k(FR)-G4.1

Medium intensity obstacle light for nighttime marking




Technical Data

Nominal Voltage	24 V / 48 V DC
Functional Voltage	19,2 V – 55 V
Ambient temperature	-40° to +55 °C
Power consumption	Peak: 16 W Average (STAC): 6 W
Max on current	1,1 A
Service lifetime	Min. 10 years
Optical characteristics red	• 2000 cd modified beam beacon (STAC)
Colour coordinates	according to ICAO
Timing	GPS based
Enclosure	Marine grade aluminum (AlMg3) EN AW-5754, anodized to 25 µm
Lens	Clear acrylic, UV-resistant
Bare weight	7,5 kg
Pressure compensation	Gore membrane vents
Size	height = 159 mm; diameter = 372 mm
Sealing	EPDM o-rings
IP-class	IP68

Pin Out

1	Power Supply +24V
2	Power Supply 0 V
3	FE
4	Modbus D1
5	Modbus D0
6	Not connected



Connector G4.1 Variant

Han 3A:

Housing	09 37 003 0301
Pin Insert	09 12 005 3001
Pins	09 33 000 6102

Recommended Cable Connector:

Housing	1x 19 37 003 1640
Pin Insert	1x 09 12 005 3101
Pins	5x 09 33 000 6202

Additional Information:

- System Integration Manual